

Combi Electra Star

Twin-head cutting-off machine




Control 01





Tilting of the moving cutting heads 02



The Emmegi twin-head cutting-off machines boast of exceptional performance characteristics, including ruggedness and reliability. This machine is the ideal tool for cutting aluminium and PVC bars in various thicknesses and at different angles. Latest generation machines which can make a considerable contribution to the production cycle thanks to their high standard of accuracy and user-friendliness. Combi Electra Star is an electronic twin-head cutting-off machine for compound cuts. It features motor-driven and electronically controlled rotation of the horizontal axis ($22^{\circ}30'$ external angles and 45° internal angles) plus pneumatic rotation of the vertical axis (45° internal angles). Blade angle of the moving cutting heads is controlled pneumatically. The machine can be provided with an industrial label printer to enable profile identification and association with relative job.



Intermediate support (optional) 03



Vertical clamps (optional) 04



The images are only given for illustrative purposes

Combi Electra Star

Twin-head cutting-off machine

01 Control

The user-friendly control panel installed on the various models, runs on bearings and allows correct positioning of the moving cutting heads according to cutting specifications.
The work cycle is optimized through creation of the cutting lists thus reducing scrap as well as workpiece loading/unloading times.

02 Tilting of the moving cutting heads


Tilting of the moving cutting heads is powered by servomotors with encoder while relative positioning is controlled electronically and parameterized by the control system.
Rotation about the vertical axis is powered by pneumatic cylinders. The moving cutting heads are fully guarded in the work zone and lowering of these guards is pneumatic.

03 Intermediate support (optional)

The pneumatic intermediate support proves highly useful when cutting light profiles with considerable lengths.
In such case the pneumatic support automatically seeks to create the ideal condition to support the profile.
This accessory is available for all lengths, but it is especially recommended on machines with cutting capacity of 5 and 6 metres.

04 Vertical clamps (optional)

Reliable and exact clamping of the profile to be cut is ensured by appropriate pneumatic clamps. Such clamps are provided with a low pressure device to avoid accidental squashing. For easier adjustment in width and height of the individual cylinders, each set of clamps is provided with practical and quick-acting level handles.



CONTROL CHARACTERISTICS	
Industrial computer "Windows XPE" compatible	
12" colour TFT graphic monitor	
1 GB DOMM memory	
Mouse built into keyboard	
Provision for connection to industrial label printer	
Provision for connection to remote PC via USB, network or serial port (depending on version)	
Execution of cyclic cuts from cutting lists and macros	
Execution of single cuts	
Memorization of 500 profile compensations with automatic calculation of the size for angle cuts	
Memorization of 500 cutting lists (1000 lines each) via keyboard	
Optimization of bars	
MACHINE CHARACTERISTICS	
Electronic control of intermediate angles	
Measurement of moving cutting head position via direct measuring system with magnetic tape	
2 carbide-tipped blades dia. 500	
Full guard for cutting zone, pneumatically operated	
Pair of horizontal pneumatic clamps with "low pressure" device	
Vertical clamping system with horizontal clamp	
Profile support roller conveyor	
Minimum quantity oil lubrication system	
Manual profile support	
Provision for automatic start of swarf exhauster MG	
Metric scale	
Cutting capacity 4/5/6 m depending on model	
Blade motor power rating (kW)	2.2