

Fit MA Hardware assembly bench



Clamping system



Hard anti-friction PVC contact surface

01

02



Correct flow of materials, whether semi-finished products or parts in the assembly phase or finished products, plays an important role in rationalizing and optimizing the production cycle. The Emmegi Logistics line offers companies a concrete solution to all storage, handling and assembly problems.

Fit MA is an assembly bench for fitting perimeter band-sawed hardware on aluminium, wood and PVC sashes.

A system of drop-away clamps grips the sash. The bench is equipped with an automatically fed screwing unit.

Pneumatic work table 03 tilting



The images are only given for illustrative purposes

Automatic screwing unit 04



Fit MA

Hardware assembly bench

01 Clamping system

A system of drop-away clamps under the work table allows centered clamping of the door or window.

02 Hard anti-friction PVC contact surface

The Hard anti-friction PVC contact surface ensures smooth movement and easy handling of the frame.

03 Pneumatic work table tilting

Thanks to the foot switch control the work table can be tilted with pneumatic movement from 0° (horizontal) to 12° for facilitating fitting of the hardware.

04 Automatic screwing unit

The screwing unit with automatic feed runs on horizontal slideways.

WORK TABLES	
Pneumatic tilting of the work table from 0° (horizontal) to 12°	0
Adjustable work table height (mm)	875 ~ 925
WORKPIECE CLAMPING	
Clamp opening (mm)	290 ~ 2.840
Adjustable clamping force, max.	740 N
Gripping system with self-centering clamping frame and drop-away bars	0
CONTACT SURFACE	
Hard anti friction PVC contact surface	٠
MISCELLANEOUS	
Characteristic "A": automatic screwing unit running on horizontal slideways	٠
Characteristic "C": band-sawing of perimeter hardware with automatic stop gauge	0
Load capacity (kg)	1960
Air consumption (NI/min)	870
Installed power (kW)	0,35

- included
 available
- 2021/01/01

www.emmegi.com