

Adjustable feet 01



Roller conveyor 02



## V-Link

Roller conveyor for frame transport



Vertical roller conveyor for easy transport of frames and fenestration products including very heavy ones between the various assembly stations.

Contact surface with scratch-proof rollers 03



The images are only given for illustrative purposes

# V-Link

Roller conveyor for frame transport

## 01

### Adjustable feet

The feet are vertically adjustable for reaching the correct height required by the work surface. They allow variable angular settings from 85° to 90°. Special holes allow anchoring to the floor.

## 02

### Roller conveyor

A bottom roller conveyor, with adjustable height from floor level in the range 320 to 360 mm, supports the workpiece weight as well as ensuring easy and smooth handling.

## 03

### Contact surface with scratch-proof rollers

Five roller tracks mounted on rods provide support to the workpiece against the inclined stand so that even very heavy windows or doors can be handled safely.

#### CHARACTERISTICS

Height, bottom roller conveyor (mm)	320 ÷ 360
Contact surfaces covered with soft PVC	•
Adjustable tilting of the work surface (°)	85 ÷ 90
Loading capacity (kg)	200
Length (mm)	3.000
Height (mm)	2.165 ÷ 3.015
Width (mm)	870
Weight (kg)	100

2021/01/01

[www.emmegi.com](http://www.emmegi.com)

The images are only given for illustrative purposes